




**MACINATORE
GRINDER
TRITURADOR**

TR 500 L Ø 260



PARTICOLARE PLC
PLC DETAIL
DETALLE PLC



CENTRALINA
OLEODINAMICA
HYDRAULIC POWER UNIT
CENTRAL HIDRÁULICA



MODELLO

TR 500 L

POTENZA ELETTRICA ROTORE ROTOR ELECTRIC POWER POTENCIA ELECTRICA DEL ROTOR	kw	9,2 – 11
POTENZA ELETTRICA CENTRALINA PLC ELECTRIC POWER POTENZIA ELETTRICA PLC	kw	0,55
LUNGHEZZA ROTORE LENGHT ROTOR LONGITUD ROTOR	mm.	500
DIAMETRO ROTORE ROTOR DIAMETER DIÁMETRO ROTOR	Ø	260
GIRI AL ROTORE ROTOR ROTATIONS ROTACIONES DE ROTOR	rpm	50 – 70
LAME BLADES LÁMINAS	n° D x D (*)	22 30 X 30
TIPO DI LAMA TYPE OF BLADES TIPO DE LÁMINAS	i / p (**)	Incava (***)
CORSA SPINTORE PUSHER RUN FUNCIONAMIENTO DEL EMPUJADOR	mm.	400
LUNGHEZZA LENGHT LONGITUD	mm.	1660
LARGHEZZA WIDTH ANCHO	mm.	960
ALTEZZA DA TERRA HEIGHT ALTURA	mm.	1650
LUNGH. BOCCA TRAMOGGIA HOPPER LENGHT LONGITUD DE LA TOLVA	mm.	930
LARGH. BOCCA TRAMOGGIA HOPPER WIDTH ANCHURA DE LA TOLVA	mm.	500
ALTEZZA TRAMOGGIA HOPPER HEIGHT ALTURA DE LA TOLVA	mm.	690
PRODUZIONE LEGNO X ORE WOOD PRODUCTION X HOUR PRODUCCIÓN MADERA X HORA	Griglia 20 mm Grid 20 mm Rejilla 20 mm	120 - 220
PESO WEIGHT PESO	Kg	850

(*) quantità x dimensione/quantity x dimension / cantidad x dimension

(**) incave/piane / i=incave/p=flat / i=incave/p=plan (***) hollow / concava

